



Approval Number

E13 92R-01 10376 TYPE 1015

Pos	Qty	Part No.	Description	Ordernumber
1	1	DFSB-T1015	Muffl. DesertFox Type 1015 Shot Blasted	BM12R10-DESB - Shot Blasted
1	1	DFCS-T1015	Muffl. DesertFox Type 1015 Carbon Steel	BM12R10-DECS - Carbon Steel
1	1	DFBL-T1015	Muffl. DesertFox Type 1015 Black Coated	BM12R10-DEBL - Black Coated
		80273	Mounting Parts:	Weight:
2	1	750004	Link Pipe	Stock: 5,0 kg
				Bos: 4,4 kg
3	1	69013	Mounting Bracket	Noiselevel: @ 3850 rpm
4	1	69014	Mounting Bracket	Stock: Specified 93,0 dB(A)
5	4	14148	M6x12 Torx Flange Screw	Measured 92,5 dB(A)
6	2	300005	M5x12 Bolt	Bos: Closed 90,5 dB(A)
7	2	300004	M5 Serrated Flanged Nut	Open 93,5 dB(A)
8	1	Original	Rubber	
9	1	64779	Spacer 9 mm.	
10	1	Original	Washer	
11	1	Original	Bolt	
12	2	14088	Pull Spring 36 mm.	Performance
13	1	14111	Speednut M5	Stock: 124,5 Hp / 7324 rpm
14	1	64780	Clamp 67 with nutcase	Bos: 125,4 Hp / 7388 rpm
15	2	Original	Bolt	Max. Hp incr.: + 3,1 Hp / 7629 rpm
16	1	600042	Heatshield	Max Nm incr.: + 3,4 Nm / 4455 rpm

Extra Parts:

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.
After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.